KAWNEER ALUMINIUM AA3720 BIFOLD DOORS

QUOTE/ORDER FORM



Enquiry please quote Order please process	Date Of Order Date Required
Contact Details	Door has to comply with Document Q of the Building Regulations
Ordered By	(additional costs apply for the PAS 24 specification product).
Company Name	Please note, 3-2-1 and 3-1-2 can comply with PAS 24).
Delivery Address	Keyed Alike
•	Bottom track detail
Postcode	45mm standard threshold - with full weather rating
Tel	24mm low threshold – not severe weather rated
Email	24mm add on 15mm coupler
Order No.	not recommended for exposed locations Stock Colour
Your Reference	
Delivery Date Requested	NAL 7010 Textured Antimacite Orey
Site Contact	Available on a longer lead time RAL 7015 Slate Grey RAL 7016 Anthracite Grey
Company Name	,
Delivery Address	RAL 9005 Black
	RAL 7016 Anthracite Grey outside/ RAL 9016 White inside
Postcode	RAL 7016 Anthracite Grey outside/ RAL 9016 Traffic White inside
Tel	Matt finish Textura finish Gloss finish
Delivery option	Other RAL Colour
Fully assembled with outer frame joints sealed	Marine Grade Finish Yes No
Kit form	Mandatory within 500 metres of the sea, tidal estuary or in a
If 6m wide or 2.2m high will be delivered in kit form	swimming pool or any other chemical or industrial environment. Please refer to our maintenance guide.
Overall frame width (mm)	1 x 5000 Aluminium trickle vent through 34mm add-on profile
Overall frame height (mm)	No Black White Grey Not Required
Door will be fitted in:	Internal Bifold Yes (Note: If bifold is internal, no drainage required).
Sheltered location Exposed location	10 Year Master Handles
Opening direction Inward Outward	White Black Grey
Flat sash as standard Round sash	Satin Silver Chrome Polished gold
Cill requirements included in overall frame height	Locking intermediate handle/s – Black D Handle as standard
104mm 159mm 199mm No cill required	White Black Grey Satin Chrome
Note: Cill platform height is 25mm included in the overall height. 10mm add leg on back edge of ci	Opening Configuration – viewed from outside
Glazing – square bead	
Glazed Unglazed	
28mm Square bead 32mm Square bead	
44mm Square bead 36mm Square bead	
28mm, Toughened, Low E, Argon Filled, Black Warm Edge Spacer	
Please refer to our sealed unit and glass limitations guidelines. Touch-up paint	 Total number of Number of sashes Sashes Folding left Folding right
Touch-up paint	

